



# ROCKFIX

## CRP-15

## Product Data Sheet



### PRODUCT DESCRIPTION

**ROCKFIX CRP-15** is solvent based formulated for Carpet application contact adhesive, based on Polychloroprene. This has been developed specially for use in tropical and hot climates.

### APPLICATION

- It can also be used for all types of flooring construction porous & non- porous surfaces.
- For fixing Carpet, Felt Backing Vinyl Floor Tiles.
- It is easy to apply by roller or brush.

### ADVANTAGES

- Good initial wet tack
- Extended setting time allowing carpet installation for adjustments
- Wider Coverage
- Economical and simple to use.
- Resistant to heat, moisture and detergent.
- Applied easily by Roll or brush
- Excellent water resistance
- Good chemical resistance

### DIRECTIONS FOR USE

Make sure that surfaces are dry, clean, free oil and grease or any foreign particles. The wet coverage of the adhesive is 4 – 6 m<sup>2</sup>/kg subject to porosity of the substrate, film thickness and nature of material being bonded. Uniformly apply the adhesive on floor using roller or brush. Application may also be applied by punching holes on the bottom of the Can Packaging and allow to flow uniformly on the floor. Allow 10 -15 minutes till sticky dry, while adjustment on carpet can be made. Apply pressure to the carpet to ensure adhesion. Allow to cure for 24 Hrs. to get good results.

### STORAGE

- Stored tightly closed in a well-ventilated area between 5°C to 39°C. Keep away from direct sunlight
- Shelf life is up to 12 months in unopened container when stored as directed

### TECHNICAL SPECIFICATION

Base	Synthetic resin + Polychloroprene
Color	Yellowish
Viscosity, Cps @25°C, S 3, rpm 20	1,000 - 1,800
Solid Content, % @110°C, 2 hr	19 – 21
Density, kg/L	0.92 – 0.98
Flash Point, °C	< +10
Open Time, min	10 - 15
Solubility	Aromatic Solvent
Cleaning	Clean all tools immediately with aromatic solvent

### HEALTH & SAFETY

As with all chemicals, caution should always be exercised. Protective clothing such as gloves and goggles should be worn.

**INHALATION:** Inhalation of vapor or mist should be avoided. If inhaled symptoms include coughing, wheezing, laryngitis, and shortness of breath, headache, nausea, and vomiting. Immediately shift victim to fresh air, and, if needed immediately start artificial respiration. Give oxygen if breathing is labored. Get emergency medical help.

**EYE CONTACT:** Flush eyes with water for 15 minutes and call for medical help.

**INGESTION:** Causes nausea, vomiting, and loss of consciousness. If accidentally swallowed do not induce vomiting rather call for medical help immediately.

**SKIN CONTACT:** Flush with water or soap and water until all traces have been removed. Seek medical attention if required.

#### WARRANTY

The information given is based on our knowledge and performance of the material. Every precaution is taken in the manufacture of the product and responsibility is limited to the quality of supplies with no guarantee of results in the field, as manufacturer has no control over site conditions or execution of work.

### UAE

Tel. +971 6 5611411  
[uae@star-uae.com](mailto:uae@star-uae.com)  
[www.star-uae.com](http://www.star-uae.com)

### KSA

Tel. +996 12 677 7073  
[kas@star-uae.com](mailto:kas@star-uae.com)  
[www.star-uae.com](http://www.star-uae.com)

### INDIA

Tel. +91 260 2220241  
[india@star-uae.com](mailto:india@star-uae.com)  
[www.star-uae.com](http://www.star-uae.com)